

# SAFETY DATA SHEET

#### 1. Identification

Product identifier LATICRETE LATAFLEX Gold Adhesive

Other means of identification None.

Recommended use of the chemical and restrictions on use

Recommended use Adhesive.

Restrictions on use Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Details of manufacturer or importer

Manufacturer

Company name LATICRETE International

Address 1 Laticrete Park, N

Bethany, CT 06524

**Telephone** (203)-393-0010

Contact person Steve Fine

Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada

1.703.527.3887

**Supplier** 

Company name LATICRETE Australia

Address P.O. Box 508

Virginia Business Mail Centre

29 Telford Street VIRGINIA QLD 4014

Australia

Telephone (61) (7) 3865-1599
Website www.laticrete.com
Emergency phone number 1.703.527.3887

## 2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Carcinogenicity Category 1A

Specific target organ toxicity following single

exposure

Specific target organ toxicity following Category 2 (lung)

repeated exposure

Not classified.

Label elements, including precautionary statements

933232 Version #: 01 Revision date: - Issue date: 13-April-2016

**Environmental hazards** 

Category 3 respiratory tract irritation

### Hazard symbol(s)



Signal word Danger

Hazard Statement(s) Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

cause cancer. May cause respiratory irritation. May cause damage to organs (lung) through

prolonged or repeated exposure.

**Precautionary Statement(s)** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove victim to fresh air

and keep at rest in a position comfortable for breathing. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification

Not classified.

Supplemental information None.

## 3. Composition/information on ingredients

#### **Mixture**

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
Portland Cement	65997-15-1	45 - 55
Silica Sand	14808-60-7	25 - 30
Carbon black	1333-86-4	3 - 9
Calcium formate	544-17-2	1 - 2

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

### 4. First-aid measures

### Description of necessary first aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician

if symptoms develop or persist.

Skin contact Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

**Eye contact** Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

centre immediately.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Personal protection for first-aid

responders

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated

clothing before reuse.

Symptoms caused by exposure Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

cause chronic effects.

Medical attention and special

LATICRETE LATAFLEX Gold Adhesive

treatment

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

## 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire

fighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes.

**Hazchem Code** 

None

General fire hazards No unusual fire or explosion hazards noted.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate

protective equipment and clothing during clean-up. Ensure adequate ventilation.

For emergency responders

Do not touch damaged containers or spilled material unless wearing appropriate protective

**Environmental precautions** 

Methods and materials for

containment and cleaning up

Avoid discharge into drains, water courses or onto the ground.

Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery,

flush area with water.

### 7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimise dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

# 8. Exposure controls and personal protection

Control parameters

Follow standard monitoring procedures.

Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	Inhalable dust.
Silica Sand (CAS	TWA	0.1 mg/m3	Respirable dust.

### Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational **Environment)**

Issue date: 13-April-2016

Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	Inspirable dust.
Silica Sand (CAS 14808-60-7)	TWA	0.1 mg/m3	

LATICRETE LATAFLEX Gold Adhesive 933232 Version #: 01

Revision date: -

### **US. ACGIH Threshold Limit Values**

Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	Inhalable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Silica Sand (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

# **UK. EH40 Workplace Exposure Limits (WELs)**

Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3.5 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	4 mg/m3	Respirable dust.
·		10 mg/m3	Inhalable dust.
Silica Sand (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.

**Biological limit values** No biological exposure limits noted for the ingredient(s).

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica **Exposure guidelines** 

should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide evewash station.

Individual protection measures, for example personal protective equipment (PPE)

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

**Hand protection** Wear chemical-resistant, impervious gloves. Wear appropriate chemical resistant clothing. Other

Respiratory protection Wear a dust mask if dust is generated above exposure limits. Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Always observe good personal hygiene measures, such as washing after handling the material Hygiene measures

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

## 9. Physical and chemical properties

**Appearance** 

Physical state Solid. **Form** Powder.

Colour Off-white to gray. Not available. Odour **Odour threshold** Not available. pН Not available. Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Flash point Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

LATICRETE LATAFLEX Gold Adhesive SDS Australia Flammability limit - upper

(%)

Not available.

Not available. Vapour pressure Vapour density Not available. Not available. Relative density

Solubility(ies)

Insoluble. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature Viscosity** Not available.

## 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

### Information on possible routes of exposure

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing.

Skin contact Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Eye contact Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.

Swallowing may cause gastrointestinal irritation. Ingestion

Symptoms related to exposure Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

cause chronic effects.

**Acute toxicity** May cause respiratory irritation.

Components **Species Test results** 

Calcium formate (CAS 544-17-2)

Acute Oral

LD50

Rat 2650 mg/kg

Carbon black (CAS 1333-86-4)

Acute Dermal

LD50 Rabbit > 3000 mg/kg

Oral

LD50 Rat > 8000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation

Respiratory sensitisation No data available.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

LATICRETE LATAFLEX Gold Adhesive

### Carcinogenicity

May cause cancer. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

### **ACGIH Carcinogens**

Carbon black (CAS 1333-86-4)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Portland Cement (CAS 65997-15-1) A4 Not classifiable as a human carcinogen.

Silica Sand (CAS 14808-60-7)

A2 Suspected human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Silica Sand (CAS 14808-60-7) 1 Carcinogenic to humans.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (lung) through prolonged or repeated exposure.

Aspiration hazard Due to the physical form of the product it is not an aspiration hazard.

Chronic effects Prolonged or repeated exposure may cause lung injury, including silicosis.

Other information Inhalation of high concentrations of guartz dust can lead to the lung disease known as silicosis,

with cough and shortness of breath.

## 12. Ecological information

**Ecotoxicity** Not expected to be harmful to aquatic organisms.

Components Species Test results

Carbon black (CAS 1333-86-4)

Aquatic Acute

Fish LC50 Leuciscus idus  $\Rightarrow$  1000 mg/l, 96 Hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available for this product.

**Mobility in soil** The product is insoluble in water and will sediment in water systems.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal methods**Dispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Residual waste

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

# 14. Transport information

**ADG** 

Not regulated as dangerous goods.

SDS Australia

### RID

Not regulated as dangerous goods.

## **IATA**

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

This substance/mixture is not intended to be transported in bulk.

# 15. Regulatory information

### Safety, health and environmental regulations

This Material Safety Data Sheet was prepared in accordance with the Australia National Code of **National regulations** 

Practice for the Preparation of Material Safety Data Sheets (NOHSC: 2011.)

### **High Volume Industrial Chemicals (HVIC)**

Carbon black (CAS 1333-86-4) 10000 - 99999 TONNES See the regulation for additional

information.

Portland Cement (CAS 65997-15-1) > 1000000 TONNES See the regulation for additional information. Silica Sand (CAS 14808-60-7)

100000 - 999999 TONNES See the regulation for additional

information.

## Importation of Ozone Deleting Substances (Customs(Prohibited imports) Regulations 1956, Schedule 10)

## National Pollutant Inventory (NPI) substance reporting list

Not listed.

#### **Prohibited Carcinogenic Substances**

Not regulated.

Prohibited Substances (National Model Regulation for the control of Workplace Hazardous Substances, Schedule 2 NOHSC:1005 (1994) as amended)

## Resricted Importation of Organochlorine Chemicals (Customs(Prohibited Imports) Regulations 1956, Schedule 9)

Not listed

### **Restricted Carcinogenic Substances**

Not regulated.

### International regulations

### **Stockholm Convention**

Not applicable.

#### **Rotterdam Convention**

Not applicable.

#### **Kyoto protocol**

Not applicable.

# **Montreal Protocol**

Not applicable.

## **Basel Convention**

Not applicable.

# International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

LATICRETE LATAFLEX Gold Adhesive Issue date: 13-April-2016 Country(s) or region Inventory name On inventory (yes/no)\*

Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes

**Philippines** Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

## 16. Other information

Issue date 13-April-2016

**Revision date** 

HSDB® - Hazardous Substances Data Bank References

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

LATICRETE LATAFLEX Gold Adhesive

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).