



UNIPRIME

Characteristics:

- Uniprime is an acrylic based universal wall / floor primer for use prior to the application of RLA/Atlas Tile adhesives, waterproofing membranes and levelling compounds.
- Uniprime increases the adhesion of RLA/Atlas Tile adhesives onto the substrate.
- Uniprime must be used to prime all absorbent surfaces including, timber floors, concrete, fibre cement sheets etc before tiling.

Preparation:

- Ensure all surfaces are sound, dry and free from excessive movement, oil, dust, grease, wax, curing compounds, release agents, paint and any other loose contaminating materials.
- For non-porous surfaces like existing tiles, sheet vinyl etc or contaminated surfaces use RLA universal primer.

Application:

- When applying the primer onto floor surfaces it is recommended to firstly pour some primer in a section then spread the primer using a broom, brush or roller. Then continue this method of application until the entire area is primed.
- Note: This method of application ensures a thorough coat of the primer on the surface.
- Allow the primer to dry for approximately 20 minutes at 20°C prior to commencing tiling / waterproofing.
- Any pools of uncured primer should be soaked up and removed with a rag.

Clean Up:

- Excess primer, tools and other equipment can be cleaned up using water while the primer is still wet.

Coverage:

- The coverage of Uniprime will vary depending upon the substrate.
- As a guide it will cover approximately 8-10m² /Litres.

Can be used with:

Tile Adhesives
Waterproofing membranes
and
Levelling compounds



Packaging / Shelf life:

- Uniprime is available in 20L, 5L, and 1L pails.
- A pail of Uniprime, when stored in a cool, dry environment, and is stored above ground level, will have a shelf life of approximately 12 months.

Handy Tips:

- Do not apply Uniprime in temperatures above 40°C and below 5°C.
- For applications / situations not mentioned in this data sheet please contact your nearest RLA/Atlas office.
- Uniprime is classified as a non-hazardous product.
- For a full MSDS on this product please contact your nearest RLA/Atlas office.

Disclaimer: The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturer's control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insists that all workmanship must be carried out in accordance with AS 3958.1-2007. It is also the responsibility of the end user to ensure that the literature in their possession is the latest issue.

Technical Data

Appearance
Drying Time @ 20°C

White liquid.
Approx 30 minutes.

Density

1.10 +/- 0.05



www.rlapolymers.com.au

TECHNICAL ENQUIRIES TOLL FREE No. 1800 752 679

Head Office:
215 Colchester Rd,
Kilsyth, VIC 3137
Ph: (03) 9728 1644
Fax: (03) 9728 6009

NSW:
363 Wentworth Ave,
Pendle Hill, NSW 2145
Ph: (02) 9636 7444
Fax: (02) 9636 7688

Queensland:
25 Computer Rd,
Yatala, QLD 4207
Ph: (07) 3807 4022
Fax: (07) 3807 4755

South Australia:
Blade Runner Distributors
2 Seaforth Ave,
Somerton Park, SA 5044
Ph: (08) 8358 5200
Fax: (08) 8358 5300

Western Australia:
Ph: 1800 242 931

New Zealand:
67 Dalgety Dr,
Manukau City
Auckland, NZ
Ph: 649 267 2772

