**LATICRETE MultiMastic #15 Tile Adhesive** TRADE NAME (as labeled): USE: Tile Adhesive MANUFACTURER'S NAME: LATICRETE PTY LTD 29 Telford Street Virginia. QLD. 4014 For additional information: 07 38651599, 1800 331 012 Web address: www.laticrete.com.au **Poisons Information Number:** 131126 Date prepared or revised: 08/05/17 Classification: Not Hazardous according to the criteria of the NOHSC. Not classified as a Dangerous Goods substance according to the ADG code. Not classified as a scheduled poison according to the SUSDP. Not classified as a flammable or combustible liquid according to the criteria of AS 1940. Risk Phrases: R36/37/38 Irritating to eyes, respiratory system and skin. R66 Repeated exposure may cause skin dryness and cracking. S24 Avoid contact with the skin. S25 Avoid contact with eyes. S25 In case of contact with the eyes, rinse immediately with Safety Phrases: plenty of water and seek medical advice. S28 After contact with skin was immediately with plenty of soap. S36/37/38 Wear suitable protective clothing, gloves and eye/face protection.

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Other ingredients determined at level not to be hazardous

**Inhalation**: Vapour may cause slight irritation to upper respiratory tract. No adverse effects are anticipated from inhalation incidental to normal exposure.

CAS NUMBERS

1317-65-3

**PERCENT** 

30-65 To 100%

Contact with eyes: Eye contact may cause slight, temporary eye irritation. If symptoms persist seek medical attention.

Contact with Skin: Short exposure not likely to cause significant skin irritation. Skin absorption is unlikely due to physical properties.

Swallowed: Single dose oral toxicity is believed to be low. No hazards anticipated from ingestion incidental to industrial exposure.

FIRST AID or EMERGENCY PROCEDURES

**CHEMICAL NAMES** 

Calcium Carbonate

#### LATICRETE MultiMastic #15

### **Material Safety Data Sheet**

**Eye Contact:** Wash the eyes with large amounts of water for 15 minutes, occasionally lifting the lower and upper lids. If symptoms persist get medical attention promptly.

**Skin Contact:** Remove contaminated clothing. Promptly wash contaminated skin with water for 3-5 minutes and then soap or mild detergent and water. If symptoms persist seek medical attention promptly.

**Inhaled:** Safely move the exposed person to fresh air at once and allow to rest. Provide artificial respiration if breathing stops. Seek medical attention unless recovery is immediate.

Swallowed: If the person is conscious, give large amounts of water. Do not induce vomiting. Get medical attention immediately.

#### First aid facilities

Provide normal industrial first aid facilities, eye wash station and safety showers as appropriate.

#### **Notes to Physician**

Possible aggravated pre-existing conditions – none reported.

Suggested treatment for acute symptoms, known antidotes – Provide care and treatment based on the patient's reaction to the exposure. For further information contact the; Poisons Information Centre 131126 in all states (New Zealand Dial 0800764766)

Chronic Health Effects: Prolonged or repeated skin exposure may lead to drying and cracking skin.

	5. FIRE FIGHT	ING MEASURES
Flash Point, °C (give method): Auto ignition temperature, °C:	Not flammable or combust N/A	ible
Flammable limits in air, volume %:	N/A Lower (LEL)	Upper (UEL)
Fire extinguishing materials: x water sprayx foam	N/A  x carbon dioxide x dry chemical	
Hazchem Code: Not allocated		
Material is not combustible. Product Special fire fighting procedures: W containers cool. Unusual fire and explosion hazards	/ear SCBA and full turn out c	ent has boiled off. lothing. Avoid body contact with substance run off. Keep fire exposed
	6. ACCIDENTA	AL RELEASE MEASURES

**Emergency Procedures – Spills and Leaks - Include employee protection measures:** Use absorbent material or scrape up dried material and place in container. Avoid unnecessary exposure and contact. Wear safety glasses and impervious gloves.

Prevent from entering drains and waterways.

Preparing wastes for disposal (container types, neutralization etc): Soak up with absorbent materials. Store in pails or drums. Bury in approved landfill or burn solid wastes in an adequate incinerator. If enters sanitary sewers, flush with large amounts of water.

Notify relevant authorities if it enters drains and waterways.

## **LATICRETE MultiMastic #15**

# **Material Safety Data Sheet**

<b>Disposal:</b> Recycle wherever possible or consult manufa and local regulations.	acturer for recycling options. Dispose of in an authorized landfill according to federal, state
7. h	HANDLING AND STORAGE
Handle with suitable protective clothing. Avoid skin or ey	ve contact.
Check all containers are clearly labeled and free from le	aks.
Storage Requirement Store in a cool, dry ventilated place between 1 -35 °C. F manufacturers storing and handling recommendations.	Protect containers against physical damage and check regularly for leaks. Observe
8. E	XPOSURE CONTROLS & PERSONAL PROTECTION
No exposure standards for this product have been s	set OR not found in our records.
Ventilation and engineering controls: If used external ventilation provide mechanical ventilation to comfort level	ally, natural ventilation is generally adequate. If used in enclosed spaced with poor els.
Respiratory protection (type): No respiratory protection vapour filters to AS1715 & AS1716 in areas with high variations.	on is should be required if good ventilation is maintained. Use respirators fitted with organic apour concentrations.
Eye protection (type): Use a chemical goggle or safety	y glasses with side shields or safety glass to AS1337.
Gloves (specify material): Use impervious gloves, vin	yl or rubber to AS2161
Other clothing and equipment: Wear clean, long-slee	eved, body covering clothing.
Work practices, hygienic practices: Familiarize the e contaminated clothing and clearing of contaminated are	employees with the handling procedures in this section; also encourage prompt removal of as.
9. P	HYSICAL AND CHEMICAL PROPERTIES
Vapor density (air=1): N/A	Melting point or range, °C: N/A
Specific gravity: 1.6	Boiling point or range, °C: 100
Solubility in water: Miscible	Evaporation rate (butyl acetate = 1): N/A
Vapor pressure, mmHg at 20 ° C: 0mm	<b>pH:</b> 10
Appearance and odour: White paste, slight acrylic odo	our
10. l	REACTIVITY DATA
Stability: X	Stable Unstable
Conditions to avoid: Excessive heat and freezing	
Incompatibility (materials to avoid): Strong oxidizers	and caustics

### **LATICRETE MultiMastic #15**

### **Material Safety Data Sheet**

Hazardous decomposition products (including combustion products): (from burning, neating or reaction with other material): None
Hazardous polymerization: May occur X Will not occur
No relevant product data found
12. ECOLOGICAL CONSIDERATIONS
May have an adverse effect on aquatic organisms if large amounts are released to waterways.
Dispose of all wastes in accordance with federal, state and local regulations for non-hazardous chemical wastes
Requirements under the ADG code, IMDG code, or the IATA DG code do not apply to this product
Label in accordance with the National Code of Practice for the Labeling of Workplace Substance (NOHSC: 2012 (1994)): Labeling under the SUSDP or the ADG Code is not required.

This information is furnished without warranty, representation, inducement, or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate. Persons dealing with the products referred to in this MSDS do so at their own risk since their actions are beyond our control. Laticrete Pty Ltd accepts no liability whatsoever for damage or injury arising from the use of the information contained in this document. This document should be made available to all operators who may come into contact with this product.