# SAFETY DATA SHEET

# **1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

### 1.1 Product identifier

Product nameCEMFLEXSynonym(s)CEM FLEX

#### 1.2 Uses and uses advised against

Use(s) CERAMIC ADHESIVE • TILE ADHESIVE

### 1.3 Details of the supplier of the product

Supplier name	DRIBOND CONSTRUCTION CHEMICALS
Address	49-57 Davis Street, Wingfield, SA, 5013, AUSTRALIA
Telephone	(08) 8243 7888
Fax	(08) 8243 7800
Email	info@constructionchemicals.com.au
Website	www.constructionchemicals.com.au

## 1.4 Emergency telephone number(s)

Emergency

(08) 8243 7888

# 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

GHS classification(s)	Skin Corrosion/Irritation: Category 2
	Serious Eye Damage / Eye Irritation: Category 2A
	Specific Target Organ Systemic Toxicity (Single Exposure): Category 3

2.2	Label	elements

Signal word

Pictogram(s)



WARNING

#### Hazard statement(s)

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

#### Prevention statement(s)

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.



#### Response statement(s) P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P312 Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment is advised - see first aid instructions. P321 P332 + P337 + P313 If skin or eye irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before re-use. Storage statement(s) P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. **Disposal statement(s)** P501 Dispose of contents/container in accordance with relevant regulations. 2.3 Other hazards

No information provided.

# 3. COMPOSITION/ INFORMATION ON INGREDIENTS

#### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ADDITIVE(S)	-	-	Remainder
PORTLAND CEMENT	65997-15-1	266-043-4	30 to 60%
RUBBER	-	-	Not Available

# 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

EyeIf in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to<br/>stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.InhalationIf inhaled, remove from contaminated area. Apply artificial respiration if not breathing.SkinIf skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.<br/>Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.IngestionFor advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If<br/>swallowed, do not induce vomiting.First aid facilitiesEye wash facilities and safety shower should be available.

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

# 5. FIRE FIGHTING MEASURES

### 5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

### 5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated.

### 5.3 Advice for firefighters

No fire or explosion hazard exists.

### 5.4 Hazchem code

None allocated.

# ChemAlert.

# 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate.

#### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

#### 6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

#### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

# 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

#### 7.3 Specific end use(s)

No information provided.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
Ingredient	Kelerence		mg/m³	ppm	mg/m³
Portland Cement	SWA (AUS)		10		

#### **Biological limits**

No biological limit values have been entered for this product.

#### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

#### PPE

Eye / FaceWear dust-proof goggles.HandsWear PVC or rubber gloves.BodyWhen using large quantities or where heavy contamination is likely, wear coveralls.RespiratoryWhere an inhalation risk exists, wear a Class P1 (Particulate) respirator. At high dust levels, wear a<br/>Powered Air Purifying Respirator (PAPR) with Class P3 (Particulate) filter or a Class P3 (Particulate)<br/>respirator.



# 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance POWDER



#### 9.1 Information on basic physical and chemical properties

Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
рН	11 (1% solution)
Vapour density	NOT AVAILABLE
Specific gravity	3
Solubility (water)	SLIGHTLY SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

# **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

#### 10.2 Chemical stability

Stable under recommended conditions of storage.

#### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

#### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

#### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

#### 10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

# **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

Acute toxicity	Information available for the product: Based on available data, the classification criteria are not met.
Skin	Contact with powder or wetted form may result in irritation, rash and dermatitis.
Eye	Contact may result in irritation, lacrimation, pain, redness, corneal burns and possible permanent damage.
Sensitisation	Not classified as causing respiratory sensitisation. However, some individuals may exhibit an allergic response upon exposure to cement, possibly due to trace amounts of chromium.
Mutagenicity	Insufficient data available to classify as a mutagen.
Carcinogenicity	This product may contain trace amounts of crystalline silica and hexavalent chromium which are classified as carcinogenic to humans (IARC Group 1). There is sufficient information to conclude that the relative risk of lung cancer from exposure to crystalline silica is increased in persons with silicosis. Therefore, preventing the onset of silicosis will also reduce the cancer risk.
Reproductive	Insufficient data available to classify as a reproductive toxin.
STOT – single exposure	Over exposure may result in irritation of the nose and throat, with coughing.
STOT – repeated exposure	Not classified as causing organ damage from repeated exposure.

# ChemAlert.

Aspiration

This product is a solid and aspiration hazards are not expected to occur.

## 12. ECOLOGICAL INFORMATION

#### 12.1 Toxicity

No information provided.

#### 12.2 Persistence and degradability

## No information provided.

#### 12.3 Bioaccumulative potential

No information provided.

#### 12.4 Mobility in soil

No information provided.

#### 12.5 Other adverse effects

No information provided.

# 13. DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

**Waste disposal** Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required).

**Legislation** Dispose of in accordance with relevant local legislation.

### 14. TRANSPORT INFORMATION

#### NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None Allocated	None Allocated	None Allocated
14.2 Proper Shipping Name	None Allocated	None Allocated	None Allocated
14.3 Transport Hazard Class	None Allocated	None Allocated	None Allocated
14.4 Packing Group	None Allocated	None Allocated	None Allocated

14.5 Environmental hazards No information provided

14.6 Special precautions for user

Hazchem code None Allocated

### **15. REGULATORY INFORMATION**

15.1 Safety, health an	d environment	al regulations/legislation specific for the substance or mixture
Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).	
Classifications	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.	
	The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardou Substances [NOHSC: 1008(2004)].	
Hazard codes	Xi	Irritant
Risk phrases	R36/37/38	Irritating to eyes, respiratory system and skin.



Safety phrases	S22 S24/25 S26 S28 S36/37/39	Do not breathe dust. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice After contact with skin, wash immediately with plenty of water. Wear suitable protective clothing, gloves and eye/face protection.
Inventory listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances)	

AUSTRALIA: AICS (Australian Inventory of Chemical Substand All components are listed on AICS, or are exempt.

# **16. OTHER INFORMATION**

Additional information	CEMENT CONTACT DERMATITIS: Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium.	
	IARC - GROUP 1 - CONFIRMED HUMAN CARCINOGEN. This product contains an ingredient for which there is sufficient evidence to have been classified by the International Agency for Research into Cancer as a human carcinogen. The use of products known to be human carcinogens should be strictly monitored and controlled.	
	employed to selection ar uncomfortab	PRS: In general the use of respirators should be limited and engineering controls o avoid exposure. If respiratory equipment must be worn ensure correct respirator and training is undertaken. Remember that some respirators may be extremely le when used for long periods. The use of air powered or air supplied respirators should and where prolonged or repeated use is necessary.
	PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.	
	HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.	
Abbreviations	ACGIH CAS # CNS EC No. EMS GHS GTEPG IARC LC50 LD50 mg/m <sup>3</sup> OEL pH ppm STEL STOT-RE STOT-RE SUSMP SWA TLV TWA	American Conference of Governmental Industrial Hygienists Chemical Abstract Service number - used to uniquely identify chemical compounds Central Nervous System EC No - European Community Number Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) Globally Harmonized System Group Text Emergency Procedure Guide International Agency for Research on Cancer Lethal Concentration, 50% / Median Lethal Concentration Lethal Dose, 50% / Median Lethal Dose Milligrams per Cubic Metre Occupational Exposure Limit relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). Parts Per Million Short-Term Exposure Limit Specific target organ toxicity (repeated exposure) Specific target organ toxicity (single exposure) Standard for the Uniform Scheduling of Medicines and Poisons Safe Work Australia Threshold Limit Value Time Weighted Average

**Report status** 

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au.

# [End of SDS]

