



# Tradies Choice – Master Additive



## DESCRIPTION

Tradies Choice Master additive is a concentrated white acrylic liquid to be used with cement based tile adhesives.

Ideal for immersed tiling applications such as swimming pools and spas etc.

Can be used with grouts to increase flexibility and strength.

Master additive can be mixed with sand and cement screeds to increase strength.



## SURFACE PREPERATION

The surface must be clean, dry, firm and free of dust, oil, grease, wax and curing compounds. The substrate must be installed according to the relevant standards and manufacturer recommendations. All porous surfaces must be primed with SAS Master Primer. For non -porous surfaces such as existing tiles, adhesives must be primed using SAS Master Primer neat. Please contact SAS Technical Team for further information.



## MIXING

### **Tiling in immersed situations**

Mix 1 part additive to 2 parts water

### **Grout additive**

Mix 1 part additive to 3 parts water

### **Sand cement screeds**

Mix 50 – 50 additive to water



## MOVEMENT JOINTS

Movement joints must be in accordance with Australian Standards AS 3958.



## PACKAGING

Master additive is available in 5L and 20L Containers.



## PRECAUTIONS

When tiling externally above 2.7m high, please contact the SAS Technical team for further information.

## TECHNICAL DATA

**Appearance – White Liquid.**

**SDS is available at [www.sas-aa.com.au](http://www.sas-aa.com.au)**



**SAS Australasia Pty Ltd**  
**1300 202 894**  
**[www.sas-aa.com.au](http://www.sas-aa.com.au)**

ABN: 83 617 827 282

P1 1-9-21

Disclaimer: The information supplied is to the best of SAS knowledge and is true and accurate. The application of the product is beyond SAS control and any alleged failure or damage must be inspected by a representative from SAS. All workman ship must be carried out in accordance with AS 3958.1-2007.