

Packaging




Mixing



Application



Uses



Substrates

Tiled floors
and walls

Waterproofs tiled areas without removing tiles

Description

A siloxane/solvent based material that penetrates deep into the grout and porous tiles, forming a water-repellent barrier.

Shower Fix is not a coating, coatings fail if chipped or scratched and wear due to ordinary cleaning. Coatings need to be reapplied constantly and once damaged fail.

Uses

Prevents moisture getting behind tiles, which can cause cracking, rusting and mould.

Features

- Clear and colourless
- Simple and fast to apply
- Allows grout and tiles to breathe
- Is not a coating, does not fail due to chips or scratches
- Do not have to remove tiles

Coverage (Approximate)

500ml will treat approximately 15m²

Performance Data

Test conducted with a moisture meter show that no moisture passes through areas that has been sealed.

Specification

The waterproofing compound shall penetrate into porous or cracked areas and stop moisture penetration, such as **Shower Fix** manufactured by **Construction Chemicals** and shall be applied in accordance with the manufacturer's application instructions.

Surface Preparation

Ensure all surfaces are visually dry and mould free (**Shower Fix** actually works more effectively with some moisture). Remove all silicone or acrylic sealant from tile joints and corners. Clean tiles and existing grout thoroughly to remove any mould or mildew. Rake out any crumbling or loose grout and replace with **Kemgrout**. Allow at least 7 days for new grout to cure sufficiently prior to treatment with **Shower Fix**.

Application

Apply liberally to tiled areas using a small brush, paying particular attention to grout lines. Almost immediately after the first application, apply a second coat 'wet on wet'. Allow approximately 5 minutes before wiping off excess with a soft cloth. Always allow 24 hours before using the shower.

Shower Fix is a clear, undetectable treatment, however it is recommended to apply to a small inconspicuous area to ensure satisfactory performance. After recommended drying **Colour Seal** or **Sealflex**, a flexible coloured acrylic sealant, to all corner joints.

Clean Up

Use mineral turps and methylated spirits.

Storage

Keep in a cool dry place away from open fires, heater and stoves, etc.

Shelf Life

2 years